



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: PDUMH15

Metered PDU / Power Distribution Unit - Safe, reliable power distribution with digital current meter

Highlights



- 1U rackmount PDU
- Digital current monitoring display
- 12 rear facing outlets, 1 front facing outlet
- 15-ft cord
- 15-amp breaker
- Switchless design

Description

Tripp Lite's PDUMH15 AC power distribution unit offers a digital current monitor and provides 15 amps of 120 volt capacity in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for wallmount, under-counter, or 1U/0U rackmount installation. Uses only 1U of rack space when installed in any 19-inch rack, with the potential for zero U mounting in the cable management area of most rack enclosures. Built-in digital ammeter display offers continuous visual power consumption data for the entire PDU. Attractive rackmount housing with 1 front and 12 rear facing outlets measures only 4.5 inches in depth. Unfiltered electrical pass-through without a power switch makes the PDUMH15 ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets, and more. Includes 12 rear facing NEMA 5-15R and one front facing outlet, 15-ft. AC power cord, 15 amp breaker, TVSS grounding lug and rugged all metal rackmount case design.

Applications

- Multi-outlet power distribution unit with digital current monitoring is the ideal means of powering multiple loads in 19 inch rackmount, wall-mount, and under-counter applications such as internetworking, PC systems, telecommunications, audio visual, security, sound reinforcement, and more. Ideal distribution of alternate and sinewave UPS and generator power or commercially derived AC power to connected equipment.

Package Includes

- PDUMH15 Metered rackmount PDU
- Owner's manual with warranty information

Features

- 120V 15A Metered rackmount AC power distribution unit with 15 amp capacity and 13 AC receptacles
- Front panel digital current monitoring display shows power consumption of connected equipment
- Versatile all-metal rackmount cabinet with detachable mounting flanges allows wall-mount, under-counter, and 19-inch rackmount mounting in both 1U and zero U formats
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- 13 NEMA 5-15R output receptacles accept common NEMA5-15P equipment plugs
- 15 foot AC power cord with NEMA5-15P plug connection
- Switch-free design prevents the potential for accidental shutoff of connected loads
- 15 amp electrical capacity with circuit breaker
- 120 VAC, 50/60 Hz electrical compatibility

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120V
Frequency compatibility	50 / 60 Hz
OUTPUT	
Output nominal voltage	120V
Outlet quantity / type	13 NEMA 5-15R
Overload protection	15A
INPUT	
Maximum input amps	15A
Input connection type	NEMA 5-15P
Input cord length	15 feet
Recommended Electrical Service	120V
LEDS ALARMS & SWITCHES	
Front panel LEDs	Digital LED current monitor display
PHYSICAL	
Shipping weight (lbs)	5.2
Shipping Dimensions (HWD/in)	2.25 x 20.5 x 10
Unit weight (lbs)	4.5
Unit Dimensions (HWD/in)	1.75 (1U) x 17.5 x 4.5
Material of construction	Sheet Metal
Form factors supported	1U rackmount, 0U vertical rackmount, wall-mount, and under-counter installation
Style	Rackmount, Vertical Rackmount, Wallmount/Under-Counter
SPECIAL FEATURES	
TVSS grounding	Rear grounding lug
Appearance	All black color scheme
CERTIFICATIONS	
Certifications	Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada), RoHS Compliant
WARRANTY	
Product Warranty Period	Lifetime

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3457.